



350 KW / 440 KVA

MODEL		TP-I350-T3-60-UL	
<p>Triton Power is a world leader in the design, manufacture of stationary, mobile and rental generator sets and Power Modules from 10 to 2000 kW. Through our commitment to quality we manufacture with only the highest quality components from companies like Cummins, John Deere, Perkins, Marathon, and Deep Sea. All of this plus our worldwide warranty, customer service professionals, is why Triton is the THE POWER OF QUALITY</p>			
Available Voltage	Standby	kVA	440
3 Phase		kW	350
120/208, 120/240, 277/480	Prime	kVA	315
Power Factor 0.8		kW	395

Standby : Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046 .

Prime : Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046.

- High quality, reliable and complete power unit
- UL-2200 LISTED
- Compact design
- Easy start and maintenance
- Every generator set is subject to a comprehensive test program which includes full load testing and checking and providing of all control and safety shut down functions testing
- Full engineered with a wide range of options and accessories:
 - Sound Attenuated Enclosure
 - Trailer with fuel tank
 - UL Listed Fuel Tank
 - Permanent Magnet Generator
 - Electronic Governor



Agency Approval: UL 508 R CSA C22.2 No 14 NFPA 110
 CE Compliance: EC LVD-73/23/EEC EN 61000-6-4:2001 EMC EN 50178:1997
 EMC- 89/336/EEC
 EN 610000 6-2:2001 EMC Immunity

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.
 All photos are representative and may not reflect exact model



ENGINE INFORMATION

ENGINE MAKE		Iveco
Model		C13TE3X
Engine Speed	RPM	1800
Fuel Type		Diesel
Engine Power Output at rated rpm	kWm	371
	HP	497
Cooling		Liquid Cooled
Aspiration		Turbocharged, Aftercooled
Total Displacement	Liter	12.88
No. of Cylinders and Build		6 Cylinder
Bore and Stroke	mm x mm	135 x 150
Injection		Direct
Governor		Electronic
Fuel Consumption (Gal/hr)	Full Load	24.21
	75% Load	18.16
	50% Load	13.62
Fuel Tank Capacity	Liter	Inquire
Oil Capacity	Liter	32
Coolant Capacity	Liter	68
Radiator Cooling Air	m³/sec	11

<p><u>Economic Power</u></p> <ul style="list-style-type: none"> Mechanically operated unit fuel injectors with electronic control, combined with carefully matched turbocharging, provide excellent fuel economy and low emissions. <p><u>Reliable Power</u></p> <ul style="list-style-type: none"> Developed and tested using the latest engineering techniques and finite element analysis for high reliability, low oil usage and low wear rates. High compression ratios ensure clean rapid starting in all conditions. 	<p><u>Certification</u></p> <ul style="list-style-type: none"> Generator set is UL2200 certified and meets ISO 8528-5 standards <p><u>Cost Effective Power</u></p> <ul style="list-style-type: none"> Compact size and low noise. Lower fuel consumption and oil use. 600 hour service intervals. 1 year warranty.
--	---

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.
 All photos are representative and may not reflect exact model



CONTROLLER INFORMATION DEEP SEA MODEL 7310

The DSE7310 is a control module for single gen-set applications. The module incorporates a number of advanced features to meet the most demanding on-site applications. The DSE7310 is an Automatic Start Control Module designed to start and stop diesel and gas generating sets that include electronic and non-electronic engines. The module includes USB, RS232 and RS485 ports as well as dedicated DSENet® terminals for expansion device connectivity. The modules are simple to operate and feature a simple menu layout for improved clarity. Enhanced features include a real time clock for enhanced event and performance monitoring, Ethernet communications for low cost monitoring, dual mutual standby to reduce engine wear and tear, and preventative maintenance features to detect engine part faults prior to a major problem occurring.

MAIN FEATURES:



NEW FEATURES

- Neutral position on breakers
- Mains current protection
- Improved mains detection 3phase 3 wire
- Additional programmable logic
- Improved modem diagnostics
- Remote control sources (10) can be accessed via SCADA

- Additional electrical trip options
 - Additional start delay functions
 - Oil pressure values from additional engines
 - Front panel editing of scheduler
 - Now displays kW as % of rated kW setting
- ### STANDARD FEATURES
- Backed up real time clock
 - True dual mutual standby with load balancing timer
 - Ethernet communications
 - Multiple date and time maintenance scheduler
 - 132 x 64 pixel LCD display
 - Configurable display languages
 - Programmable event logging (250), showing reason, date and time
 - Robust module enclosure
 - Five key menu navigation
 - Durable soft touch membrane buttons
 - Fully configurable via PC software
 - LED and LCD alarm indication
 - Engine exercise mode

- Configurable start & fuel outputs
 - kWh monitoring
 - Automatic load transfer
 - Configurable inputs
 - Configurable outputs
 - Configurable timers and alarms
 - Modbus RTU
 - Magnetic pick-up
- ### Selected front panel programming
- Multiple date and time exercise scheduler
 - Configurable display pages
 - Programmable load shedding/acceptance
 - Mutual standby
 - Preventative maintenance
 - kW overload protection
 - 3 alternative configurations
 - Unbalanced load protection
 - SMS messaging (external modem required)
 - Power save mode
 - Security levels - PC software has password system to control access to PC software features
 - Configuration file downloads from an external memory device
 - RS232 & RS485 comm communications
 - DSENet® compatible

BENEFITS

- 132 x 64 pixel ratio makes information easy to read
- Real time clock provides accurate event logging
- PC software is license free
- Set maintenance periods can be configured to maintain optimum engine performance
- Ethernet communications provides advanced remote monitoring at low cost
- Modules can be integrated into building management systems
- Preventative maintenance avoids expensive engine down time
- Advanced PCB layout ensures high reliability

OPERATION

The module is operated using the front STOP/RESET, MANUAL, AUTO, TEST and START pushbuttons. An additional pushbutton next to the LCD display is used to scroll through the modules metering displays.



ALTERNATOR INFORMATION

Manufacturer	Stamford
Design	Brushless single bearing, revolving field
Stator	2/3 pitch
Rotor	Single bearing, flexible disc
Insulation System	Class H
Standard Temperature Rise	125 -163°C Continuous
Exciter Type	Self Excited
Phase Rotation	A (U), B (V), C (W)
Alternator Cooling	Direct drive centrifugal blower fan
AC Waveform Total Harmonic Distortion	No load < 1.5%. Non distorting balanced linear load < 5%
Telephone Influence Factor (TIF)	<50 per NEMA MG1-22.43
Telephone Harmonic Factor (THF)	<2%

STANDARD ITEMS


- Mainline Circuit Breaker
- Generator Set mounted on Heavy Duty Steel Base Frame
- Anti-Vibration Pads between Engine/Alternator and Frame
- Forklift Pockets within Base Frame (up to 400 kW)
- Battery Charging Alternator

OPTIONAL ITEMS

ENGINE OPTIONS	<ul style="list-style-type: none"> • Engine Block Heater • Racor Fuel Water Separator • Oil Heater
ALTERNATOR OPTIONS	<ul style="list-style-type: none"> • Permanent Magnet Generator • Anti-Condensation Heater • Oversized Alternator (Motor Starting)
OTHER OPTIONS	<ul style="list-style-type: none"> • Sound Attenuated Enclosure with Critical Silencer (72 db at 7 meters) • Trailer (with or without fuel tank) • UL-142 Base Mounted Fuel Tank • Residential or Critical Grade Silencer




WEIGHT AND DIMENSIONS



SKID MOUNTED GENERATOR

DIMENSIONS (LxWxH)	In	130.3 x 54.7 x 70.8
DRY WEIGHT	Lb	6832



SOUND ATTENUATED GENERATOR

DIMENSIONS (LxWxH) without TANK	In	171.3 x 55.1 x 77
DRY WEIGHT	lb	9845

FEATURES AND BENEFITS OF ENCLOSURE:

- | | |
|--|---|
| <ul style="list-style-type: none"> All enclosure parts are modular No welding to reduce corrosion Doors on both sides for easy maintenance All metal parts are powder coated | <ul style="list-style-type: none"> Critical Exhaust Silencer Included Thermally insulated exhaust system Emergency stop located on exterior Easy Lifting and Moving |
|--|---|

	<p>TRITON POWER CORP 8511 NW 61 STREET MIAMI, FL USA Phone: 305-592-6300 Fax: 305-592-5900 E-mail: info@tritonpower.com www.americasgenerators.com</p> <p style="font-size: small;">Triton Power is a subsidiary of Americas Generators, Inc.</p>
--	--

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.
 All photos are representative and may not reflect exact model